

HIGH PERFORMANCE ECO-FRIENDLY PRODUCTS

ENVIROWASH

FORMULA

805

CONCENTRATE

PRODUCT DESCRIPTION:

SENTINEL® 805™ is specifically formulated and highly concentrated. It has been designed to meet both HUD Guidelines and Phosphate rules for Maryland and New York. It can be used for lead dust and mercury clean-up and for final surface preparation of sub-floors following mastic removal on asbestos abatement jobs.

REMOVES LEAD
HIGHLY CONCENTRATED
ASPHALT ADHESIVE CLEAN-UP

DIRECTIONS: (Always follow product label instructions for best results.)

FOR LEAD ABATEMENT: Mix 1 part 805 to 20 parts of water to meet HUD recommended dilution ratio (approximately 1 quart of 805 to gallons of water). 805 should be used before encapsulating, after active abatement has concluded and for general maintenance in reducing exposure to lead dust.

To Use: Wash all surfaces, ceilings, walls, floors, windows, doors, fixtures, cabinets, etc. with EnviroWash solution. Starting with the ceiling, work down to the floor. The cleaning solution should be changed (at least) after each room has been washed, and more often in larger areas. Each time the mixture is changed, workers must ensure that the used water does not re-contaminate the environment. 805 may be applied with sponges, rags or mops, depending on the area to be cleaned. Protect exposed skin and eyes, especially when working overhead. Rinse if necessary. Try Sentinel EnviroTowels if cross-contamination, mixing and diluting, or lack of water is a problem.

FOR ASPHALT ADHESIVE RESIDUE REMOVAL: Mix from 5 to 10 parts of water to 1 part of 805, depending on the amount of residue left following adhesive removal. Pour mixture onto the floor to be cleaned. Use a broom, manual stripper pad or rotating floor scrubber with stripper pads to scrub the floor until clean. Wash and rinse the floor, changing the water as needed to ensure a clean surface. Allow to dry before resurfacing.



For additional information or assistance with this product, please call Sentinel Customer Service at, 800-373-0633.

SPECIFICATIONS:

APPEARANCE	GREEN
APPROXIMATE BOILING POINT	215-290°F
ODOR	NONE
SPECIFIC GRAVITY (TEMP)	(60°F) .806
FLASHPOINT	NONE
pH	10.25

800-373-0633
www.senpro.com

Sentinel Products, Inc
8901 Wyoming Ave. N.
Brooklyn Park MN 55445